


Interference Suppression Film Capacitors MKP Radial Potted Type



Dimensions in mm
 (1) $|F - F'| < 0.3 \text{ mm}$
 $F = 7.5 + 0.6/-0.1 \text{ mm}$

APPLICATIONS

For standard across the line X2 applications.
 See also application note:
www.vishay.com/docs/28153/anaccaps.pdf

REFERENCE STANDARDS

"IEC 60384-14 ed-3 and EN 60384-14
 "IEC 60065, pass. flamm. class B"
 CSA-C22.2 No. 1; UL1414
 CSA-E384-14; UL1283; CQC

MARKING

C-value; tolerance; rated voltage; sub-class; manufacturer's type designation; code for dielectric material, manufacturer location; manufacturer's logo; year and week; safety approvals

DIELECTRIC

Polypropylene film

ELECTRODES

Metallized film

CONSTRUCTION

Mono construction

FEATURES

7.5 to 27.5 mm lead pitch. Supplied loose in box, taped on ammpack or reel

RoHS compliant product

RATED VOLTAGE

AC 310 V; 50 to 60 Hz

PERMISSIBLE DC VOLTAGE

DC 630 V

ENCAPSULATION

Plastic case, epoxy resin sealed, flame retardant UL-class 94 V-0

CLIMATIC TESTING CLASS ACC. TO IEC 60068-1

55/110/56/B

CAPACITANCE RANGE (E12 SERIES)

E12 series 0.001 to 4.7 μF
 Preferred values acc. to E6

CAPACITANCE TOLERANCE

$\pm 20 \%$; $\pm 10 \%$; $\pm 5 \%$

LEADS

Tinned wire

MAXIMUM APPLICATION TEMPERATURE

$C \leq 470 \text{ nF}$: 110 °C (125 °C for less than 1000 h)
 $C > 470 \text{ nF}$: 110 °C

DETAIL SPECIFICATION

For more detailed data and test requirements contact:


RFI@vishay.com



RoHS
COMPLIANT



COMPOSITION OF CATALOG NUMBER



TYPE	PACKAGING	STANDARD DIMENSIONS	C-TOL	CODE NUMBER		
339 X2	Loose in box	Lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm	± 20 %	BFC2 339 20...		
		Lead length 5.0 ± 1.0 mm		BFC2 339 22...		
		Lead length 25.0 ± 2.0 mm		BFC2 339 24...		
	Taped (1)	Reel: H = 18.5 mm; P ₀ = 12.7 mm or 15.0 mm		± 10 %	BFC2 339 26...	
		Ammopack: H = 18.5 mm; P ₀ = 12.7 mm			BFC2 339 28...	
		Reel: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm			BFC2 339 56...	
	Ammopack: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm	BFC2 339 58...				
	Loose in box	Lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm			± 5 %	BFC2 339 10...
		Lead length 5.0 ± 1.0 mm				BFC2 339 12...
		Lead length 25.0 ± 2.0 mm	BFC2 339 14...			
	Taped (1)	Reel: H = 18.5 mm; P ₀ = 12.7 mm or 15.0 mm	BFC2 339 16...			
		Ammopack: H = 18.5 mm; P ₀ = 12.7 mm	BFC2 339 18...			
		Reel: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm	BFC2 339 66...			
	Loose in box	Lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm	± 10 %	BFC2 339 68...		
		Lead length 5.0 ± 1.0 mm		BFC2 339 50...		
		Lead length 25.0 ± 2.0 mm		BFC2 339 52...		
	Taped (1)	Reel: H = 18.5 mm; P ₀ = 12.7 mm or 15.0 mm		BFC2 339 54...		
		Ammopack: H = 18.5 mm; P ₀ = 12.7 mm		BFC2 339 36...		
		Reel: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm		BFC2 339 38...		
	Loose in box	Lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm		± 5 %	BFC2 339 76...	
		Lead length 5.0 ± 1.0 mm			BFC2 339 78...	
		Lead length 25.0 ± 2.0 mm			BFC2 339 80...	
	Taped (1)	Reel or ammpack: H = 18.5 mm; P ₀ = 12.7 mm	BFC2 339 21...			
		Ammopack: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm	BFC2 339 23...			
Reel: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm		BFC2 339 25...				
Loose in box	Lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm	± 20 %	BFC2 339 27...			
	Lead length 5.0 ± 1.0 mm		BFC2 339 11...			
	Lead length 25.0 ± 2.0 mm		BFC2 339 13...			
Taped (1)	Reel or ammpack: H = 18.5 mm; P ₀ = 12.7 mm		± 10 %	BFC2 339 15...		
	Ammopack: H = 18.5 mm; P ₀ = 12.7 mm			BFC2 339 17...		
	Reel: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm			BFC2 339 51...		
Loose in box	Lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm			± 5 %	BFC2 339 53...	
	Lead length 5.0 ± 1.0 mm				BFC2 339 55...	
	Lead length 25.0 ± 2.0 mm				BFC2 339 46...	
Taped (1)	Reel: H = 18.5 mm; P ₀ = 12.7 mm or 15.0 mm	± 20 %	BFC2 339 48...			
	Ammopack: H = 18.5 mm; P ₀ = 12.7 mm		BFC2 339 29...			
	Reel: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm		BFC2 339 31...			
Loose in box	Lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm		± 10 %		BFC2 339 33...	
	Lead length 5.0 ± 1.0 mm				BFC2 339 35...	
	Lead length 25.0 ± 2.0 mm				BFC2 339 37...	
Taped (1)	Reel: H = 18.5 mm; P ₀ = 12.7 mm or 15.0 mm	± 5 %		BFC2 339 39...		
	Ammopack: H = 18.5 mm; P ₀ = 12.7 mm			BFC2 339 41...		
	Reel: pitch 7.5 mm (bent back), H = 16.0 mm; P ₀ = 15.0 mm			BFC2 339 43...		

Notes

(1) For detailed tape specification refer to Packaging Information: www.vishay.com/docs/28139/packinfo.pdf

(2) SPQ = Standard Packaging Quantity



SPECIFIC REFERENCE DATA

DESCRIPTION	VALUE
Rated AC voltage (U_{Rac})	310 V
Permissible DC voltage (U_{Rdc})	630 V
Tangent of loss angle:	at 1 kHz at 10 kHz
$C < 470 \text{ nF}$	$\leq 10 \times 10^{-4}$ $\leq 20 \times 10^{-4}$
$470 \text{ nF} \leq C \leq 1 \text{ }\mu\text{F}$	$\leq 20 \times 10^{-4}$ $\leq 70 \times 10^{-4}$
$C > 1 \text{ }\mu\text{F}$	$\leq 30 \times 10^{-4}$ -
Rated voltage pulse slope $(dU/dt)_R$ at 435 Vdc	100 V/ μs
R between leads, for $C \leq 0.33 \text{ }\mu\text{F}$ at 100 V; 1 min	$> 15\,000 \text{ M}\Omega$
RC between leads, for $C > 0.33 \text{ }\mu\text{F}$ at 100 V; 1 min	$> 5000 \text{ s}$
R between leads and case; 100 V; 1 min	$> 30\,000 \text{ M}\Omega$
Withstanding (DC) voltage (cut off current 10 mA); rise time 100 V/s:	
$C \leq 1 \text{ }\mu\text{F}$	2200 V; 1 min
$C > 1 \text{ }\mu\text{F}$	1800 V; 1 min
Withstanding (AC) voltage between leads and case	2120 V; 1 min
Max. application temperature for $0.001 \text{ }\mu\text{F} \leq C \leq 0.47 \text{ }\mu\text{F}$	110 °C (125 °C for less than 1000 h)
Max. application temperature for $C > 0.47 \text{ }\mu\text{F}$	110 °C

Pitch: 7.5 mm; C-tol = 20 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽²⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK ⁽¹⁾	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			$l_t =$ 3.5 + 1/- 0.5 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 7.5 ± 0.4 mm; d_t = 0.50 ± 0.05 mm									
0.001			20102	22102		24102		28102	
0.0015			20152	22152		24152		28152	
0.0022			20222	22222		24222		28222	
0.0033			20332	22332		24332		28332	
0.0047			20472	22472		24472		28472	
0.0068	4.0 x 9.0 x 10.0	0.4	20682	22682	1500	24682	1000	28682	1250
0.01			20103	22103		24103		28103	
0.015			20153	22153		24153		28153	
0.022			20223	22223		24223		28223	
0.033			20333	22333		24333		28333	
0.047	5.0 x 10.5 x 10.0	0.4	20473	22473	1000	24473	1250	28473	1000
0.068	6.0 x 11.5 x 10.0	0.8	20683	22683	750	24683	1000	28683	750

Notes

⁽¹⁾ H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

⁽²⁾ Weight for short lead product only

MKP 339 X2



Vishay BCcomponents

Interference Suppression Film Capacitors
MKP Radial Potted Type

Pitch: 7.5 mm bent back (only taped); C-tol = ± 20 %

C (μF)	DIMENSIONS w x h' x l (mm)	MASS (g) ⁽²⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING			
			LOOSE IN BOX			
			AMMOPACK		REEL (500 mm) ⁽¹⁾	
			H = 16.0 mm P ₀ = 15.0 mm	SPQ	H = 16.0 mm P ₀ = 15.0 mm	SPQ
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.60 ± 0.06 mm						
0.1	6.0 x 14.0 x 12.5	1.1	58104	1000	56104	1500
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.60 ± 0.06 mm						
0.15	6.0 x 14.0 x 17.5	1.4	-	-	56154	800
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.60 ± 0.06 mm						
0.22	7.0 x 15.5 x 17.5	1.8	-	-	56224	700
0.33	8.5 x 17.0 x 17.5	2.4	-	-	56334	550
0.47	10.0 x 18.5 x 17.5	3.0	-	-	56474	500

Notes

⁽¹⁾ Reel diameter = 356 mm, is available on request

⁽²⁾ Weight for short lead product only

Pitch: 7.5 mm; C-tol = 10 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽²⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK ⁽¹⁾	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			l _t = 3.5 + 1/- 0.5 mm	l _t = 5.0 ± 1.0 mm	SPQ	l _t = 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 7.5 ± 0.4 mm; d_t = 0.50 ± 0.05 mm									
0.001	4.0 x 9.0 x 10.0	0.45	10102	12102		14102		18102	
0.0012			10122	12122		14122		18122	
0.0015			10152	12152		14152		18152	
0.0018			10182	12182		14182		18182	
0.0022			10222	12222		14222		18222	
0.0027			10272	12272		14272		18272	
0.0033			10332	12332		14332		18332	
0.0039			10392	12392		14392		18392	
0.0047			10472	12472		14472		18472	
0.0056			10562	12562	1500	14562	1000	18562	1250
0.0068			10682	12682		14682		18682	
0.0082			10822	12822		14822		18822	
0.01			10103	12103		14103		18103	
0.012			10123	12123		14123		18123	
0.015			10153	12153		14153		18153	
0.018			10183	12183		14183		18182	
0.022			10223	12223		14223		18223	
0.027	10273	12273		14273		18273			
0.033	5.0 x 10.5 x 10.0	0.6	10333	12333		14333		18333	
0.039			10393	12393	1000	14393	1250	18393	1000
0.047			10473	12473		14473		18473	
0.056	6.0 x 11.5 x 10.0	0.8	10563	12563	750	14563	1000	18563	750

Notes

⁽¹⁾ H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

⁽²⁾ Weight for short lead product only



Interference Suppression Film Capacitors Vishay BCcomponents
MKP Radial Potted Type

Bent back pitch: 7.5 mm (only taped); C-tol = ± 10 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽²⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING			
			LOOSE IN BOX			
			AMMOPACK		REEL (500 mm) ⁽¹⁾	
			H = 16.0 mm P ₀ = 15.0 mm	SPQ	H = 16.0 mm P ₀ = 15.0 mm	SPQ
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.60 ± 0.06 mm						
0.068	5.0 x 13.0 x 12.5	0.9	68683	1300	66683	1900
0.082	6.0 x 14.0 x 12.5	1.1	68823	1000	66823	1500
0.1			68104		66104	
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.60 ± 0.06 mm						
0.12	6.0 x 14.0 x 17.5	1.4	-	-	66124	800
0.15			66154			
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.80 ± 0.08 mm						
0.18	7.0 x 15.5 x 17.5	1.8	-	-	66184	700
0.22			66224			
0.27	8.5 x 17.0 x 17.5	2.4	-	-	66274	550
0.33			66334			
0.39	10.0 x 18.5 x 17.5	3.0	-	-	66394	500
0.47			66474			

Notes

(1) Reel diameter = 356 mm, is available on request.

(2) Weight for short lead product only

Pitch: 7.5 mm; C-tol = ± 5 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽²⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING							
			LOOSE IN BOX				AMMOPACK ⁽¹⁾			
			Short leads			Long leads			H = 18.5 mm P ₀ = 12.7 mm	
			$l_t =$ 3.5 + 1/- 0.5 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ	
Pitch = 7.5 ± 0.4 mm; d_t = 0.50 ± 0.05 mm										
0.001	4.0 x 9.0 x 10.0	0.45	50102	52102		54102		38102		
0.0012			50122	52122		54122		38122		
0.0015			50152	52152		54152		38152		
0.0018			50182	52182		54182		38182		
0.0022			50222	52222		54222		38222		
0.0027			50272	52272		54272		38272		
0.0033			50332	52332		54332		38332		
0.0039			50392	52392		54392		38392		
0.0047			50472	52472	1500	54472	1000	38472	1250	
0.0056			50562	52562		54562		38562		
0.0068			50682	52682		54682		38682		
0.0082			50822	52822		54822		38822		
0.01			50103	52103		54103		38103		
0.012			50123	52123		54123		38123		
0.015			50153	52153		54153		38153		
0.018			50183	52183		54183		38183		
0.022			50223	52223		54223		38223		
0.027			50273	52273		54273		38273		
0.033	50333	52333		54333		38333				
0.039	50393	52393	1000	54393	1250	38393	1000			
0.047	50473	52473		54473		38473				
0.056	50563	52563	750	54563	1000	38563	750			

Notes

(1) H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

(2) Weight for short lead product only

Bent back pitch: 7.5 mm (only taped); C-tol = ± 5 %

C (μ F)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽²⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING			
			LOOSE IN BOX			
			AMMOPACK		REEL (500 mm) ⁽¹⁾	
			H = 16.0 mm P ₀ = 15.0 mm	SPQ	H = 16.0 mm P ₀ = 15.0 mm	SPQ
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.60 ± 0.06 mm						
0.068	5.0 x 13.0 x 12.5	0.9	78683	1300	76683	1900
0.082	6.0 x 14.0 x 12.5	1.1	78823	1000	76823	1500
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.60 ± 0.06 mm						
0.1	5.0 x 13.0 x 17.5	1.0	78104	1250	76104	1100
0.12	6.0 x 14.0 x 17.5	1.4	-	-	76124	800
0.15					76154	
Bent back pitch = 7.5 ± 0.4 mm; d_t = 0.80 ± 0.08 mm						
0.18	7.0 x 15.5 x 17.5	1.8	-	-	76184	700
0.22	8.5 x 17.0 x 17.5	2.4	-	-	76224	550
0.27					76274	
0.33					76334	
0.39	10.0 x 18.5 x 17.5	3.0	-	-	76394	500

Notes

⁽¹⁾ Reel diameter = 356 mm, is available on request

⁽²⁾ Weight for short lead product only

Pitch: 10.0 mm; C-tol = ± 20 %

C (μ F)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING								
			LOOSE IN BOX					AMMOPACK ⁽¹⁾		LARGE REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm		H = 18.5 mm P ₀ = 15.0 mm	
			l _t = 3.5 + 1/- 0.5 mm	l _t = 5.0 ± 1.0 mm	SPQ	l _t = 25.0 ± 2.0 mm	SPQ		SPQ		SPQ
Pitch = 10.0 ± 0.4 mm; d_t = 0.60 ± 0.06 mm											
0.001	4.0 x 10.0 x 12.5	0.6	21102	23102		25102		27102			
0.0015			21152	23152		25152		27152			
0.0022			21222	23222		25222		27222			
0.0033			21332	23332		25332		27332			
0.0047			21472	23472		25472		27472			
0.0068			21682	23682	1000	25682	1250	27682	950		
0.01			21103	23103		25103		27103			
0.015			21153	23153		25153		27153			
0.022			21223	23223		25223		27223			
0.033			21333	23333		25333		27333			
0.047			21473	23473		25473		27473			
0.068			5.0 x 11.0 x 12.5	0.82	21683	23683	1000	25683	1000	27683	750
0.1	6.0 x 12.0 x 12.5	1.1	20104	22104	750	24104	750	28104	600	26104	1500

Notes

⁽¹⁾ H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

⁽²⁾ Reel diameter = 356 mm is available on request

⁽³⁾ Weight for short lead product only



Interference Suppression Film Capacitors Vishay BCcomponents
MKP Radial Potted Type

Pitch: 10.0 mm; C-tol = ± 10 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING								
			LOOSE IN BOX					AMMOPACK ⁽¹⁾		LARGE REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm		H = 18.5 mm P ₀ = 15.0 mm	
			l _t = 3.5 + 1/- 0.5 mm	l _t = 5.0 ± 1.0 mm	SPQ	l _t = 25.0 ± 2.0 mm	SPQ		SPQ		SPQ
Pitch = 10.0 ± 0.4 mm; d _t = 0.60 ± 0.06 mm											
0.001	4.0 x 10.0 x 12.5	0.6	11102	13102	1000	15102	1250	17102	950	-	
0.0012			11122	13122		15122		17122			
0.0015			11152	13152		15152		17152			
0.0018			11182	13182		15182		17182			
0.0022			11222	13222		15222		17222			
0.0027			11272	13272		15272		17272			
0.0033			11332	13332		15332		17332			
0.0039			11392	13392		15392		17392			
0.0047			11472	13472		15472		17473			
0.0056			11562	13562		15562		17562			
0.0068			11682	13682		15682		17682			
0.0082			11822	13822		15822		17822			
0.01			11103	13103		15103		17103			
0.012			11123	13123		15123		17123			
0.015			11153	13153		15153		17153			
0.018			11183	13183		15183		17183			
0.022			11223	13223		15223		17223			
0.027	11273	13273	15273	17273							
0.033	11333	13333	15333	17333							
0.039	11393	13393	15393	17393							
0.047	11473	13473	15473	17473							
0.056	5.0 x 11.0 x 12.5	0.82	11563	13563	1000	15563	1000	17563	750	16683	1900
0.068			10683	12683		14683		18683			
0.082	6.0 x 12.0 x 12.5	1.1	10823	12823	750	14823	750	18823	600	16823	1500
0.1			10104	12104		14104		18104			

Notes

⁽¹⁾ H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

⁽²⁾ Reel diameter = 356 mm is available on request

⁽³⁾ Weight for short lead product only

Pitch: 10.0 mm; C-tol = ± 5 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING								
			LOOSE IN BOX					AMMOPACK ⁽¹⁾		LARGE REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm		H = 18.5 mm P ₀ = 15.0 mm	
			$l_t =$ 3.5 + 1/- 0.5 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ		SPQ
Pitch = 10.0 ± 0.4 mm; d _t = 0.60 ± 0.06 mm											
0.001	4.0 x 10.0 x 12.5	0.6	51102	53102	1000	55102	1250	48102	950	-	
0.0012			51122	53122		55122		48122			
0.0015			51152	53152		55152		48152			
0.0018			51182	53182		55182		48182			
0.0022			51222	53222		55222		48222			
0.0027			51272	53272		55272		48272			
0.0033			51332	53332		55332		48332			
0.0039			51392	53392		55392		48392			
0.0047			51472	53472		55472		48473			
0.0056			51562	53562		55562		48562			
0.0068			51682	53682		55682		48682			
0.0082			51822	53822		55822		48822			
0.01			51103	53103		55103		48103			
0.012			51123	53123		55123		48123			
0.015			51153	53153		55153		48153			
0.018			51183	53183		55183		48183			
0.022			51223	53223		55223		48223			
0.027			51273	53273		55273		48273			
0.033			51333	53333		55333		48333			
0.039			51393	53393		55393		48393			
0.047	51473	53473	55473	48473							
0.056	5.0 x 11.0 x 12.5	0.82	51563	53563	1000	55563	1000	48563	750	46683	1900
0.068			50683	52683		54683		38683		36104	
0.082	6.0 x 12.0 x 12.5	1.1	50823	52823	750	54823	750	38823	600	36823	1500

Notes

⁽¹⁾ H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

⁽²⁾ Reel diameter = 356 mm is available on request

⁽³⁾ Weight for short lead product only



Interference Suppression Film Capacitors Vishay BCcomponents
MKP Radial Potted Type

Pitch: 15.0 mm; C-tol = ± 20 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 15 ± 0.4 mm; d_t = 0.60 ± 0.06 mm									
0.01	5.0 x 11.0 x 17.5	1	90001	90007	1250	90014	1000	90021	1100
0.015			90002	90008		90015		90022	
0.022			90003	90009		90016		90023	
0.033			90004	90011		90017		90024	
0.047			90005	90012		90018		90025	
0.068			90006	90013		90019		90026	
0.1			21104	23104		25104		27104	
0.15	6.0 x 12.0 x 17.5	1.4	20154	22154	1000	24154	1000	26154	900
Pitch = 15 ± 0.4 mm; d_t = 0.80 ± 0.08 mm									
0.22	7.0 x 13.5 x 17.5	1.8	20224	22224	750	24224	500	26224	800
0.33	8.5 x 15.0 x 17.5	2.4	20334	22334	750	24334	500	26334	650
0.47	10.0 x 16.5 x 17.5	3	20474	22474	500	24474	450	26474	600
0.47	8.5 x 17.5 x 17.8	3.1	90165	90166	300	90143	500	-	-
0.56	10.0 x 18.5 x 17.8	4.3	90174	90175	225	90176	350	-	-
0.68	11.0 x 18.5 x 17.8	5.5	90168	90169	225	90145	350	-	-

Notes

- (1) H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

MKP 339 X2



Vishay BCcomponents

Interference Suppression Film Capacitors
MKP Radial Potted Type

Pitch: 15.0 mm; C-tol = ± 10 %

C (μ F)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 15 ± 0.4 mm; d_t = 0.60 ± 0.06 mm									
0.01	5.0 x 11.0 x 17.5	1.0	90027	90039	1250	90052	1000	90064	1100
0.012			90028	90041		90053		90065	
0.015			90029	90042		90054		90066	
0.018			90031	90043		90055		90067	
0.022			90032	90044		90056		90068	
0.027			90033	90045		90057		90069	
0.033			90034	90046		90058		90071	
0.039			90035	90047		90059		90072	
0.047			90036	90048		90061		90073	
0.056			90037	90049		90062		90074	
0.068			11683	13683		15683		17683	
0.082			11823	13823		15823		17823	
0.1			11104	13104		15104		17104	
0.12	6.0 x 12.0 x 17.5	1.4	10124	12124	1000	14124	1000	16124	900
0.15			10154	12154		14154		16154	
Pitch = 15 ± 0.4 mm; d_t = 0.80 ± 0.08 mm									
0.18	7.0 x 13.5 x 17.5	1.8	10184	12184	750	14184	500	16184	800
0.22			10224	12224		14224		16224	
0.27	8.5 x 15.0 x 17.5	2.4	10274	12274	750	14274	500	16274	650
0.33			10334	12334		14334		16334	
0.33	9.3 x 14.0 x 18.3	2.9	-	-	-	74334	500	-	-
0.39	10.0 x 16.5 x 17.5	3.0	10394	12394	500	14394	450	16394	600
0.47			10474	12474		14474		16474	
0.56	10.0 x 18.5 x 17.8	4.3	90167	90157	225	90144	400	-	-

Notes

- (1) H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only



Interference Suppression Film Capacitors Vishay BCcomponents
MKP Radial Potted Type

Pitch: 15.0 mm; C-tol = ± 5 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 15 ± 0.4 mm; d_t = 0.60 ± 0.06 mm									
0.01	5.0 x 11.0 x 17.5	1.0	90221	90232	1250	90243	1000	90254	1100
0.012			90222	90233		90244		90255	
0.015			90223	90234		90245		90256	
0.018			90224	90235		90246		90257	
0.022			90225	90236		90247		90258	
0.027			90226	90237		90248		90259	
0.033			90227	90238		90249		90261	
0.039			90228	90239		90251		90262	
0.047			90229	90241		90252		90263	
0.056			90231	90242		90253		90264	
0.068			51683	53683		55683		46683	
0.082			51823	53823		55823		46823	
0.1			50104	52104		54104		36104	
0.12	6.0 x 12.0 x 17.5	1.4	50124	52124	1000	54124	1000	36124	900
0.15			50154	52154		54154		36154	
Pitch = 15 ± 0.4 mm; d_t = 0.80 ± 0.08 mm									
0.18	7.0 x 13.5 x 17.5	1.8	50184	52184	750	54184	500	36184	800
0.22	8.5 x 15.0 x 17.5	2.4	50224	52224	750	54224	500	36224	650
0.27			50274	52274		54274		36274	
0.33			50334	52334		54334		36334	
0.39	10.0 x 16.5 x 17.5	3.0	50394	52394	500	54394	450	36394	600

Notes

- (1) H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

Pitch: 22.5 mm; C-tol = ± 20 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 22.5 ± 0.4 mm; d_t = 0.80 ± 0.08 mm									
0.15	6.0 x 15.5 x 26.0	2.4	21154	23154	300	25154	250	27154	600
0.22			21224	23224		25224		27224	
0.33			21334	23334		25334		27334	
0.47	7.0 x 16.5 x 26.0	2.9	21474	23474	200	25474	250	27474	500
0.68	8.5 x 18.0 x 26.0	3.8	20684	22684	200	24684	250	26684	450
1.0	10.0 x 19.5 x 26.0	6.8	20105	22105	200	24105	200	26105	350
1.5	12.3 x 22.3 x 26.3	10	90103	90138	140	90139	400	90141	300

Notes

- (1) H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

Pitch: 22.5 mm; C-tol = ± 10 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			l _t = 3.5 ± 0.3 mm	l _t = 5.0 ± 1.0 mm	SPQ	l _t = 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 22.5 ± 0.4 mm; d_t = 0.80 ± 0.08 mm									
0.12	6.0 x 15.5 x 26.0	2.4	11124	13124	300	15124	250	17124	600
0.15			11154	13154		15154		17154	
0.18			11184	13184		15184		17184	
0.22			11224	13224		15224		17224	
0.27			11274	13274		15274		17274	
0.33			11334	13334		15334		17334	
0.33	8.4 x 14.0 x 26.3	3.6	-	-	-	75334	800	-	-
0.39	7.0 x 16.5 x 26.0	2.9	11394	13394	200	15394	250	17394	500
0.47			11474	13474		15474		17474	
0.47	8.4 x 14.0 x 26.3	3.6	-	-	-	75474	800	-	-
0.56	8.5 x 18.0 x 26.0	3.8	10564	12564	200	14564	250	16564	450
0.68	10.0 x 19.5 x 26.0	6.8	10684	12684	200	14684	200	16684	350
0.82			10824	12824		14824		16824	
1.0	12.0 x 22.0 x 26.0	7.8	10105	12105	150	14105	200	16105	300

Notes

⁽¹⁾ H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

⁽²⁾ Reel diameter = 356 mm is available on request

⁽³⁾ Weight for short lead product only

Pitch: 22.5 mm; C-tol = ± 5 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽³⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm) ^{(1) (2)}	
			Short leads			Long leads		H = 18.5 mm P ₀ = 12.7 mm	
			l _t = 3.5 ± 0.3 mm	l _t = 5.0 ± 1.0 mm	SPQ	l _t = 25.0 ± 2.0 mm	SPQ		SPQ
Pitch = 22.5 ± 0.4 mm; d_t = 0.80 ± 0.08 mm									
0.12	6.0 x 15.5 x 26.0	2.4	51124	53124	300	55124	250	46124	600
0.15			51154	53154		55154		46154	
0.18			51184	53184		55184		46184	
0.22			51224	53224		55224		46224	
0.27			51274	53274		55274		46274	
0.33			51334	53334		55334		46334	
0.39	7.0 x 16.5 x 26.0	2.9	51394	53394	200	55394	250	46394	500
0.47	8.5 x 18.0 x 26.0	3.8	51474	53474	200	55474	250	46474	450
0.56			50564	52564		54564		36564	
0.68	10.0 x 19.5 x 26.0	6.8	50684	52684	200	54684	200	36684	350
0.82			50824	52824		54824		36824	
1.0	12.0 x 22.0 x 26.0	7.8	50105	52105	150	54105	200	36105	300

Notes

⁽¹⁾ H = In-tape height; P₀ = Sprocket hole distance; for detailed specifications refer to packaging information

⁽²⁾ Reel diameter = 356 mm is available on request

⁽³⁾ Weight for short lead product only



Interference Suppression Film Capacitors Vishay BCcomponents
MKP Radial Potted Type

Pitch: 27.5 mm; C-tol = ± 20 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽¹⁾	CATALOG NUMBER BFC2 33 AND PACKAGING				
			LOOSE IN BOX				
			Short leads			Long leads	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ
Pitch = 27.5 ± 0.4 mm; dt = 0.80 ± 0.08 mm							
0.47	9.0 x 19.0 x 31.0	5.5	90076	90078	100	90081	150
0.68			21684	23684		25684	
1.0	11.0 x 21.0 x 31.0	7.4	21105	23105	100	25105	125
1.5	13.0 x 23.0 x 31.0	9.2	20155	22155	100	24155	125
2.2	15.0 x 25.0 x 31.0	12.3	20225	22225	100	24225	125
3.3	18.0 x 28.0 x 31.0	16.1	20335	22335	100	24335	100
4.7	21.0 x 31.0 x 31.0	20.3	20475	22475	50	24475	75

Notes

⁽¹⁾ Weight for short lead product only

Pitch: 27.5 mm; C-tol = ± 10 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽¹⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING				
			LOOSE IN BOX				
			Short leads			Long leads	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ
Pitch = 27.5 ± 0.4 mm; dt = 0.80 ± 0.08 mm							
0.68	9.0 x 19.0 x 31.0	5.5	11684	13684	100	15684	150
0.82			11824	13824		15824	
1.0	11.0 x 21.0 x 31.0	7.4	11105	13105	100	15105	125
1.2	13.0 x 23.0 x 31.0	9.2	10125	12125	100	14125	125
1.5			10155	12155		14155	
1.8	15.0 x 25.0 x 31.0	12.3	10185	12185	100	14185	125
2.2	18.0 x 28.0 x 31.0	16.1	10225	12225	100	14225	100
2.7			10275	12275		14275	
3.3	21.0 x 31.0 x 31.0	20.3	10335	12335	50	14335	75
3.9			10395	12395		14395	

Notes

⁽¹⁾ Weight for short lead product only





Pitch: 27.5 mm; C-tol = ± 5 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) ⁽¹⁾	CATALOG NUMBER BFC2 339..... AND PACKAGING				
			LOOSE IN BOX				
			Short leads			Long leads	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ
Pitch = 27.5 ± 0.4 mm; dt = 0.80 ± 0.08 mm							
0.68	9.0 x 19.0 x 31.0	5.5	51684	53684	100	55684	150
0.82			51824	53824		55824	
1.0	11.0 x 21.0 x 31.0	7.4	51105	53105	100	55105	125
1.2	13.0 x 23.0 x 31.0	9.2	50125	52125	100	54125	125
1.5			50155	52155		54155	
1.8	15.0 x 25.0 x 31.0	12.3	50185	52185	100	54185	125
2.2	18.0 x 28.0 x 31.0	16.1	50225	52225	100	54225	100
2.7			50275	52275		54275	
3.3	21.0 x 31.0 x 31.0	20.3	50335	52335	50	54335	75

Notes

⁽¹⁾ Weight for short lead product only

APPROVALS

SAFETY APPROVALS X2	VOLTAGE	VALUE	FILE NUMBERS
EN 60384-14 (ENEC) (= IEC 60384-14 ed-3)	310 Vac	1 nF to 4.7 μ F	FI 2008038
UL1414 and CSA-C22.2 No. 1	250 Vac	1 nF to 1 μ F	E112471
UL1283	305 Vac	1 nF to 4.7 μ F	E109565
CSA-E384-14	310 Vac	1 nF to 4.7 μ F	pending
CQC	310Vac	1 nF to 4.7 μ F	CQC 07001021281 (L) CQC03001006960 (s) CQC 06001018290 (F)
CB Test Certificate	310 Vac	1 nF to 4.7 μ F	FI 5123
The ENEC-approval together with the CB-Certificate replace all national marks of the following countries (they have already signed the ENEC-Agreement): Austria; Belgium; Czech.Republic; Denmark; Finland; France; Germany; Greece; Hungary; Ireland; Italy; Luxembourg; Netherlands; Norway; Portugal; Slovenian; Spain; Sweden; Switzerland and United Kingdom.			
			

MOUNTING

Normal Use

The capacitors are designed for mounting on printed circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to "Packaging Information". www.vishay.com/docs/28139/packinfo.pdf

Specific Method of Mounting to Withstand Vibration and Shock


In order to withstand vibration and shock tests, it must be insured that the stand-off pins are in good contact with the printed circuit board:

- For pitches ≤ 15 mm capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped.

Space Requirements on Printed Circuit Board

The maximum length and width of film capacitors is shown in the drawing:

- Eccentricity as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned
- Product height with seating plane as given by "IEC 60717"
as reference: $h_{max.} \leq h + 0.3$ mm or $h_{max.} \leq h' + 0.3$ mm.



Storage Temperature

- Storage temperature: $T_{stg} = -25$ to $+40$ °C with RH maximum 80 % without condensation

Ratings and Characteristics Reference Conditions


Unless otherwise specified, all electrical values apply to an ambient temperature of 23 ± 1 °C, an atmospheric pressure of 86 to 106 kPa and a relative humidity of 50 ± 2 %.

For reference testing, a conditioning period shall be applied over 96 ± 4 hours by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.




CHARACTERISTICS


Capacitance as a function of ambient temperature (typical curve)




Impedance as a function of frequency (typical curve)




Target of loss angle as a function of frequency (typical curve)




Resonant frequency as a function of capacitance (typical curve)



Max RMS voltage as a function of frequency (typical curve)




Max. RMS current as a function of frequency (typical curve)





Insulation resistance as a function of ambient temperature (typical curve)



APPLICATION NOTES

- For X2 electromagnetic interference suppression in **standard across the line applications** (50/60 Hz) with a maximum mains voltage of 310 Vac.
- For series impedance applications we refer to application note www.vishay.com/docs/28153/anaccaps.pdf
- These capacitors are not intended for continuous pulse application. For these situations capacitors of the AC and pulse programs must be used.
- The maximum ambient temperature must not exceed 110 °C (125 °C for less than 1000 h) for C ≤ 470 nF and 110 °C for C > 470 nF.
- Rated voltage pulse slope:
If the pulse voltage is lower than the rated voltage, the values of the specific reference data can be multiplied by 435 Vdc and divided by the applied voltage.

INSPECTION REQUIREMENTS

GENERAL NOTES

1. Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, IEC publication IEC 60384-14 ed-3 and specific reference data.

Group C inspection requirements

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1		
4.1 Dimensions (detail) Initial measurements	Capacitance Tangent of loss angle: For C ≤ 1 μF at 10 kHz For C > 1 μF at 1 kHz	As specified in section “General data” of this specification
4.3 Robustness of terminations	Tensile: load 10 N; 10 s Bending: load 5 N; 4 x 90°	No visible damage



Interference Suppression Film Capacitors Vishay BCcomponents
MKP Radial Potted Type


SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
4.4 Resistance to soldering heat 4.19 Component solvent resistance 4.4.2 Final measurements	No pre-drying Method: 1A Solder bath: 280 °C ± 5 °C Duration: 10 s Isopropylalcohol at room temperature Method: 2 Immersion time: 5 ± 0.5 min Recovery time: Min. 1 h, max. 2 h Visual examination Capacitance Tangent of loss angle Insulation resistance	No visible damage Legible marking $ \Delta C/C \leq 5\%$ of the value measured initially. Increase of tan δ : ≤ 0.008 for: $C \leq 1 \mu\text{F}$ or ≤ 0.005 for: $C > 1 \mu\text{F}$ Compared to values measured initially As specified in section "Insulation Resistance" of this specification
SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1		
Initial measurements 4.20 Solvent resistance of the marking 4.6 Rapid change of temperature 4.6.1 Inspection 4.7 Vibration 4.7.2 Final inspection 4.9 Shock	Capacitance Tangent of loss angle: For $C \leq 1 \mu\text{F}$ at 10 kHz For $C > 1 \mu\text{F}$ at 1 kHz Isopropylalcohol at room temperature Method: 1 Rubbing material: cotton wool Immersion time: 5 ± 0.5 min $\theta A = - 55 \text{ }^\circ\text{C}$ $\theta B = + 110 \text{ }^\circ\text{C}$ 5 cycles Duration $t = 30 \text{ min}$ Visual examination Mounting: see section "Mounting" of this specification Procedure B4 Frequency range: 10 to 55 Hz Amplitude: 0.75 mm or Acceleration 98 m/s ² (whichever is less severe) Total duration 6 h Visual examination Mounting: see section "Mounting" for more information Pulse shape: half sine Acceleration: 490 m/s ² Duration of pulse: 11 ms	No visible damage Legible marking No visible damage No visible damage

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
4.9.2 Final measurements	Visual examination Capacitance Tangent of loss angle Insulation resistance	No visible damage $ \Delta C/C \leq 5\%$ of the value measured initially. Increase of $\tan \delta$: ≤ 0.008 for: $C \leq 1 \mu\text{F}$ or ≤ 0.005 for: $C > 1 \mu\text{F}$ Compared to values measured initially As specified in section "Insulation Resistance" of this specification
SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B		
4.11 Climatic sequence 4.11.1 Initial measurements 4.11.2 Dry heat 4.11.3 Damp heat cyclic Test Db First cycle 4.11.4 Cold 4.11.5 Damp heat cyclic Test Db remaining cycles 4.11.6 Final measurements	Capacitance Measured in 4.4.2 and 4.9.2 Tangent of loss angle: Measured initially in C1A and C1B Temperature: 110 °C Duration: 16 h Temperature: - 55 °C Duration: 2 h Visual examination Capacitance Tangent of loss angle Voltage proof 1350 Vdc; 1 min between terminations Insulation resistance	No visible damage Legible marking $ \Delta C/C \leq 5\%$ of the value measured in 4.11.1. Increase of $\tan \delta$: ≤ 0.008 for: $C \leq 1 \mu\text{F}$ or ≤ 0.005 for: $C > 1 \mu\text{F}$ Compared to values measured in 4.11.1. No permanent breakdown or flash-over $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification
SUB GROUP C2		
4.12 Damp heat steady state 4.12.1 Initial measurements	56 days; 40 °C; 90 to 95 % RH no load Capacitance Tangent of loss angle: at 1 kHz	



Interference Suppression Film Capacitors Vishay BCcomponents
MKP Radial Potted Type

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
4.12.3 Final measurements	Visual examination Capacitance Tangent of loss angle Voltage proof 1350 Vdc; 1 min between terminations Insulation resistance	No visible damage Legible marking $ \Delta C/C \leq 5\%$ of the value measured in 4.12.1. Increase of $\tan \delta$: ≤ 0.008 for: $C \leq 1 \mu\text{F}$ or ≤ 0.005 for: $C > 1 \mu\text{F}$ Compared to values measured in 4.12.1. No permanent breakdown or flash-over $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification
SUB-GROUP C3		
4.13.1 Initial measurements 4.13 Impulse voltage 4.14 Endurance 4.14.7 Final measurements	Capacitance Tangent of loss angle: For $C \leq 1 \mu\text{F}$ at 10 kHz For $C > 1 \mu\text{F}$ at 1 kHz 3 successive impulses, full wave, peak voltage: X2: 2.5 kV for $C \leq 1 \mu\text{F}$ X2: 2.5 kV/ \sqrt{C} for $C > 1 \mu\text{F}$ Max. 24 pulses Duration: 1000 h 1.25 x U_{Rac} at 110 °C Once in every hour the voltage is increased to 1000 V_{rms} for 0.1 s via resistor of $47 \Omega \pm 5\%$ Visual examination Capacitance Tangent of loss angle Voltage proof 1350 Vdc; 1 min between terminations. 2120 Vac; 1 min between terminations and case. Insulation resistance	No self healing breakdowns or flashover No visible damage Legible marking $ \Delta C/C \leq 10\%$ compared to values measured in 4.13.1. Increase of $\tan \delta$: ≤ 0.008 for: $C \leq 1 \mu\text{F}$ or ≤ 0.005 for: $C > 1 \mu\text{F}$ Compared to values measured in 4.13.1. No permanent breakdown or flash-over $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
SUB-GROUP C4		
<p>4.15 Charge and discharge</p> <p>4.15.1 Initial measurements</p> <p>4.15.3 Final measurements</p>	<p>10 000 cycles charged to 435 Vdc Discharge resistance: $R = \frac{435 \text{ Vdc}}{1.25 \times C (dU/dt)}$</p> <p>Capacitance Tangent of loss angle: For C ≤ 1 μF at 10 kHz For C > 1 μF at 1 kHz</p> <p>Capacitance</p> <p>Tangent of loss angle</p> <p>Insulation resistance</p>	<p>$\Delta C/C \leq 10\%$ compared to values measured in 4.15.1.</p> <p>Increase of tan δ: ≤ 0.008 for: C ≤ 1 μF or ≤ 0.005 for: C > 1 μF Compared to values measured in 4.15.1.</p> <p>≥ 50 % of values specified in section “Insulation Resistance” of this specification</p>
SUB-GROUP C5		
4.16 Radio frequency characteristic	Resonance frequency	≥ 0.9 times the value as specified in section “Resonant Frequency” of this specification.
SUB-GROUP C6		
<p>4.17 Passive flammability Class B</p>	<p>Bore of gas jet: Ø 0.5 mm Fuel: butane Test duration for actual volume V in mm³: V ≤ 250: 10 s 250 < V ≤ 500: 20 s 500 < V ≤ 1750: 30 s V > 1750: 60 s One flame application</p>  <p style="text-align: center;">CBA434</p>	<p>After removing test flame from capacitor, the capacitor must not continue to burn for more than 10 s. No burning particle must drop from the sample.</p>
SUB-GROUP C7		
4.18 Active flammability	20 cycles of 2.5 kV discharges on the test capacitor connected to U _{Rac}	<p>The cheese cloth around the capacitors shall not burn with a flame.</p> <p>No electrical measurements are required.</p>



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.