

Axial Cemented Wirewound Resistors



FEATURES

- All welded construction
- Non flammable cement coating
- Ceramic core
- Various kinds of lead forming available
- Lead (Pb)-free
- Pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes
- Compliant to RoHS directive 2002/95/EC



RoHS
COMPLIANT
GREEN
(5-2008)**

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	POWER RATING $P_{40\text{ }^\circ\text{C}}$	RESISTANCE RANGE ⁽¹⁾		TOLERANCE
		TCR = - 10 ... - 80 ppm/K WM 50 (Class 1)	TCR = 100 ... 180 ppm/K WM 110 (Class 3)	
Z301	1 W	0.30 Ω to 270 Ω	0.68 Ω to 2 k Ω	$\pm 10\%$, $\pm 5\%$
ZDA0411	2 W	0.47 Ω to 560 Ω	1.50 Ω to 4.30 k Ω	$\pm 10\%$, $\pm 5\%$
ZDV0411	2 W	0.47 Ω to 560 Ω	1.50 Ω to 4.30 k Ω	$\pm 10\%$, $\pm 5\%$
Z302	3 W	0.10 Ω to 510 Ω	1.80 Ω to 3.30 k Ω	$\pm 10\%$
		0.10 Ω to 510 Ω	24 Ω to 3.30 k Ω	$\pm 5\%$
		0.22 Ω to 510 Ω	-	$\pm 2\%$
		1 Ω to 510 Ω	-	$\pm 1\%$
Z303	4 W	0.10 Ω to 1 k Ω	1.80 Ω to 3.90 k Ω	$\pm 10\%$
		0.10 Ω to 1 k Ω	12 Ω to 3.90 k Ω	$\pm 5\%$
		0.10 Ω to 1 k Ω	-	$\pm 2\%$
		1 Ω to 1 k Ω	-	$\pm 1\%$
Z305	6 W	0.10 Ω to 2.4 k Ω	3.90 Ω to 10 k Ω	$\pm 10\%$
		0.10 Ω to 2.4 k Ω	10 Ω to 10 k Ω	$\pm 5\%$
		0.62 Ω to 2.4 k Ω	-	$\pm 2\%$, $\pm 1\%$
Z306	8 W	0.13 Ω to 4.7 k Ω	6.80 Ω to 16 k Ω	$\pm 10\%$, $\pm 5\%$
		1 Ω to 4.7 k Ω	-	$\pm 2\%$
		2.2 Ω to 4.7 k Ω	-	$\pm 1\%$
Z307	10 W	0.20 Ω to 8.2 k Ω	12 Ω to 30 k Ω	$\pm 10\%$, $\pm 5\%$
		1.80 Ω to 8.2 k Ω	-	$\pm 2\%$
		3.30 Ω to 8.2 k Ω	-	$\pm 1\%$

Note

⁽¹⁾ Resistance value to be selected for $\pm 10\%$ tolerance from E12 and for $\pm 5\%$, $\pm 2\%$ and $\pm 1\%$ from E24

** Please see document "Vishay Material Category Policy": www.vishay.com/doc?99902




PART NUMBER AND PRODUCT DESCRIPTION																	
Part Number: Z32041411509K2C000																	
Z	3	2	0	4	1	4	1	1	5	0	9	K	2	C	0	0	0
MODEL			TCR/MATERIAL			VALUE			TOLERANCE CODE			PACKAGING CODE		SPECIAL			
Z310309 = Z301 ZDA0411 = ZDA0411 ZDV0411 = ZDV0411 Z320414 = Z302 Z330617 = Z303 Z350922 = Z305 Z360933 = Z306 Z370947 = Z307			1 = - 10 ... - 80 ppm/K WM 50 Class 1 3 = 100 ... 180 ppm/K WM 110 Class 3 4 = SWI (special winding)			3 digit value 1 digit multiplier MULTIPLIER F = *10 ⁻⁴ 7 = *10 ⁻³ 8 = *10 ⁻² 9 = *10 ⁻¹ 0 = *10 ⁰ 1 = *10 ¹ 2 = *10 ²			F = ± 1.0 % G = ± 2.0 % J = ± 5.0 % K = ± 10.0 %			(See Packaging table)		The 5 digit BV number will be encoded using a 36 character code. This code contains numbers 0...9 and letters A...Z (36 characters total) and allows to encode at least 46 655 five digit BV numbers. 000 = Standard			
Product Description: Z302 1 15R 10 % AC G53																	
Z302			1			15R			10 %			AC G53					
MODEL (1)			TCR/MATERIAL (1)			VALUE (1)			TOLERANCE CODE (1)			PACKAGING DESCRIPTION (2)					

Notes

- (1) See "Part Number" above
- (2) See "Packaging Table"

PACKAGING TABLE										
MODEL	TAPE/LEAD LENGTH (mm)	AMMO PACK			REEL			LOOSE		
		PCS	PACKAGING CODE	PACKAGING DESCRIPTION	PCS	PACKAGING CODE	PACKAGING DESCRIPTION	PCS	PACKAGING CODE	PACKAGING DESCRIPTION
Z301	53	1000	21	A1 G53	7500	DS	RS R53			
					2000	D2	R2 R53			
Z302	53	500	2C	AC G53	7500	DS	RS R53			
					4000	24	A4 G53			
	63	4000	25	A4 G63						
	73	500	4C	AC G73						
	83	500	6C	AC G83	1000	H1	R1 R83			
					7500	HS	RS R83			
	94							500	LC	LC
108				7500	JS	RS R108				
Z303	53	500	2C	AC G53	1000	D1	R1 R53			
	83	500	6C	AC G83	1000	H1	R1 R83			
	94									
Z305	83	100	6A	AA G83						
		250	6B	AB G83	500	HC	RC R83			
Z306	83	250	6B	AB G83	500	HC	RC R83			
Z307	120							200	LJ	LJ
ZDA0411	73	1000	41	A1 G73	2000	F2	R2 R73			
ZDV0411	73	2000	40	A2 G73						


DIMENSIONS



For packaging dimensions see appropriate catalog or web page.

MODEL	DIMENSIONS in millimeters [inches]				
	A _{max.}	B _{max.}	C _{max.}	G	MASS (g)
Z301	8.5 [0.355]	3 [0.118]	0.7 [0.027]	53 ± 1 [2.087 ± 0.039]	0.5
ZDA0411	11 [0.433]	4 [0.157]	0.7 [0.027]	53 ± 1 [2.087 ± 0.039]	0.8
Z302	13 [0.512]	4.8 [0.189]	0.8 [0.031]	53 ± 1 [2.087 ± 0.039]	1.1
Z303	15.8 [0.622]	5.5 [0.217]	0.8 [0.031]	53 ± 1 [2.087 ± 0.039]	1.4
Z305	22.3 [0.878]	8.7 [0.343]	0.8 [0.031]	83 ± 1 [3.268 ± 0.039]	3.7
Z306	32.3 [1.272]	8.7 [0.343]	0.8 [0.031]	83 ± 1 [3.268 ± 0.039]	5
Z307	49.8 [1.961]	9 [0.354]	0.8 [0.031]	120 ± 2 [4.724 ± 0.079]	7





DIMENSIONS ZDV0411



DIMENSIONS in millimeters			TOL.
Lead Ø	d	0.6	
Pitch of components	P	12.7	± 1.0
Pitch of sprocket holes ⁽¹⁾	P ₀	12.7	± 0.3
Distance between hole center and resistor center	P ₁	3.85	± 0.7
Distance between hole center and lead center	P ₂	6.35	± 0.7
Lead spacing	F	5	+ 0.6, - 0.1
Angle of Insertion	Δh ₁	2 max.	-
Width of carrier tape	W	18.0	+ 1, - 0.5
Width of adhesive tape	W ₀	12.0	± 0.5
Position of holes	W ₁	9	+ 0.75, - 0.5
Position of adhesive tape	W ₂	0.5	+ 0, - 0.5
Body to hole center	H	16.0	± 0.5
Lead crimp to hole center ⁽²⁾	H ₀	19.5	± 1.0
Hole Ø	D ₀	4.0	± 0.2
Thickness of tape ⁽³⁾	t	0.9 max.	-
Height of cutting	L	11 max.	-
Height of insertion	H ₁	32.3 max.	-

Notes

- (1) Test over 10 holes - 9 intervals P₀ 12 x 9 = 114.3 ± 0.5
- (2) Parallelism, < 0.5 mm
- (3) Thickness of carrier tape: 0.55 mm ± 0.1



PERFORMANCE	
TEST	PERMISSIBLE CHANGE
Climatic category (LCT/UCT/Days)	40/200/56
Climatic sequence, IEC 60115-1, 4.23	$\Delta R = \pm (3\% R + 0.05 \Omega)$
Damp heat, steady state, IEC 60115-1, 4.24 (40 ± 2) °C, 56 days, (93 ± 3) % RH	$\Delta R = \pm (3\% R + 0.1 \Omega)$
Endurance at room temperature (116 % P_{70}), 1000 h, IEC 60115-1, 4.25.2	$\Delta R = \pm (3\% R + 0.1 \Omega)$
Storage at UCT, 1000 h, no load, IEC60115-1,4.25.3	$\Delta R = \pm (3\% R + 0.1 \Omega)$
Resistance to soldering heat, IEC 60115-1, 4.18 (260 ± 5) °C, (10 ± 1) s	$\Delta R = \pm (0.5\% R + 0.05 \Omega)$
Robustness of Termination, IEC 60115-1, 4.16 10N	$\Delta R = \pm (0.5\% R + 0.05 \Omega)$
Short time overload, IEC 60115-1, 4.13 10 x rated power for 5 s	$\Delta R = \pm (1\% R + 0.1 \Omega)$



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.